



High bay is the ideal light source for energy-efficient, low maintenance illumination in large spaces. Designed with durability and functionality in mind, the LED Round High Bay lighting options are versatile and suited to satisfy most all long-term lighting needs. The IMHB05 delivers ultra-high luminous flux for use in large indoor environments with a clearance of more than 30 feet. Its high luminous efficiency features cost savings for customers and is favored by customers compared with similar products. The IMHB05 is ideal for industrial and manufacturing applications, and is your LED replacement for up to 1000W IMH fixtures.



SPECIFICATION

Construction

- Durable, die-cast aluminum housing with heat dissipating fins.
- Dark bronze polyester powder-coat finish.
- Easy access to the driver compartment from the face.

Optics

- Efficiency higher than 171lm/W, designed to replace 750W and 1000W MH while consumes 350W and 420W.
- Light engines are available in standard 4000K- 5000K configurations.
- 120 degree lens guarantees light intensity and light uniformity.

Electrical

- Universal 120-277 VAC or 347-480 VAC input voltage.
- 0-10V dimming standard for a dimming range of 100% to 10%.
- Operating temperature is -40°C (-40°F) to 55°C (131°F) when Wattage is above 300W (Max. 65°C (149°F) for 300W and below).

Mounting

- 3/4" Conduit pendant, Hook mounting.

Controls

- Optional PIR Sensor or Bluetooth Smart Control Sensor available for further energy-saving.
- Optional Wattage Adjustment Dial allows more flexibility to suit for higher ambient or various light output requirement.

Lifespan

- Estimated 100,000-hour LED lifespan based on IES LM-80 results and TM-21 calculations.

Warranty

- 10-year limited warranty.

Certifications

- UL cUL wet location listed.

Note

- Actual performance may differ as a result of end-user environment and application. All values are design or typical values, measured under laboratory conditions at 25°C(±5°C) specifications subject to change without notice.




PERFORMANCE DATA

| SETTING | CRI | 350W | | | TEMPERATURE |
|---------|-----|--------------|---------|---------|-------------|
| | | SYSTEM WATTS | LUMENS | LPW | |
| 100% | 70 | 350W | 60000lm | 171lm/W | 55°C |
| 80% | 70 | 280W | 49000lm | 175lm/W | 65°C |
| 60% | 70 | 210W | 38000lm | 181lm/W | 65°C |
| 40% | 70 | 140W | 26000lm | 186lm/W | 65°C |

| SETTING | CRI | 420W | | | TEMPERATURE |
|---------|-----|--------------|---------|---------|-------------|
| | | SYSTEM WATTS | LUMENS | LPW | |
| 100% | 70 | 420W | 70000lm | 167lm/W | 55°C |
| 80% | 70 | 336W | 57000lm | 170lm/W | 55°C |
| 60% | 70 | 252W | 44000lm | 175lm/W | 65°C |
| 40% | 70 | 168W | 30000lm | 179lm/W | 65°C |

DIMENSION

unit: mm/inch



ACCESSORIES (Optional)

| | |
|---|---|
|  |  |
| Plug-and-Play PIR Sensor PIR sensor: ANT-6-4T Bluetooth PIR sensor: ANT-6-4T-BLE-SR | Plug-and-Play Microwave Sensor Microwave sensor: ANT-5-4T Bluetooth microwave sensor: ANT-5-4T-BLE-SR |

MOUNTING

| | |
|--|-----------------------|
|  | Hook Mount |
|  | Conduit Pendant Mount |

ORDERING GUIDE

Example: IMHB05350W27V50KYYYY

| | Fixture Type | Wattage | Voltage | CCT | Finish | Sensor (Option) | Adjustment Dial (Option) | Internal Code |
|-----|----------------------|----------------------|------------------------------|------------------------|-------------------------------------|---------------------------------------|--|-----------------------|
| IUS | <input type="text"/> | <input type="text"/> | <input type="text"/> | <input type="text"/> | <input type="text"/> | <input type="text"/> | <input type="text"/> | <input type="text"/> |
| I | MHB05 High Bay | 350W 420W | 27V 120-277V 48V 347-480V | 40K 4000K 50K 5000K | D Dark Bronze B Black W White | M With Sensor Blank Without Sensor | AD With Adjustment Dial Blank Without Adjustment Dial | Blank Alphanumeric |